```
/*linux/init/main.c*Copyright(C)1991,1992LinuxTorvalds*GK2/5/95-ChangedtosupportmountingrootfsviaNFS*Addedinitrd:backgroundcopbyGregorySmithSrlemon,Feb'96*Magnearylkjfgccisold,avoidingbogusKernels-PaulGortmaker, May'96*SimplifiedstartingofinitMichae
la.Griffith<m1ff@acm.org>,Apr'96,-REMHEL-STSCALLS*#include<linux/config.h>#include<linux/proto.h>#include<linux/ioport.h>#include<linux/hdreg.h>#include<linux/dirent.h>#include<linux/fs.h>#include<linux/tty.h>#include<linux/time.h>#include<linux/mm.h>#include<linux/kernel.h>#include<linux/stat.h>#include<linux/mount.h>#include<linux/init.h>#include<linux/pci.h>#include<linux/smp_lock.h>#include<linux/blkdev.h>#include<linux/sysrq.h>#include<linux/delay.h>#include<linux/utsrelease.h>#include<linux/utsname.h>#include<linux/rootdev.h>#include<linux/highuid.h>#include<linux/writeback.h>#include<linux/cdrom.h>#include<linux/hdreg.h>#include<linux/initrd.h>#include<linux/bootmem.h>#include<linux/tqueue.h>#include<linux/serial.h>#include<linux/serial_reg.h>#include<linux/bootmem.h>#include<linux/acpi.h>#include<linux/tty.h>#include<linux/ide.h>#include<linux/console.h>#include<linux/console_struct.h>#include<linux/vt_kern.h>#include<linux/kbd_kern.h>#include<linux/kbd_diacr.h>#include<linux/vt.h>#include<linux/selection.h>#include<linux/ctype.h>#include<linux/ioport.h>#include<linux/sysrq.h>#include<linux/kmod.h>#include<linux/kernel_stat.h>#include<linux/ptrace.h>#include<linux/sysctl.h>#include<linux/sysrq.h>#include<linux/ioport.h>#include<linux/kmod.h>#include<linux/kernel_stat.h>#include<linux/ptrace.h>#include<linux/sysctl
```